



HSM[®]

Great Products, Great People.

V-Press 605 Eco

The HSM V-Press 605 reduces the volume of soft plastic / plastic film as well as cardboard and paper in an economical way.

FEATURES

- Low installation height and small footprint.
- Special retaining claws optimise the compression of the pressing material, increasing both the loading volume and bale output.
- Quick and easy press assembly.
- Mechanical bale ejector.
- High process reliability due to HSM TCS (Torsion Control System).
- Configuration: eco-double door with hand wheel door lock.
- Convenient membrane keypad with text display, which shows the current status of the machine.

NOTE: We have a range of strapping available for this machine.

TECHNICAL INFORMATION

Pressing power:	57 kN
Specific pressing power:	11,85 N/cm ²
Driving power:	1,5 kW
Voltage / Frequency:	400 V / 50 Hz
Cycle time when idle empty:	21 s
Volume throughput in idle operation (theor.):	4,38 m ³ /h
Loading height:	655 mm
Loading aperture width x height:	800 x 495 mm
Width x Depth x Height:	1198 x 823 x 1986 mm
Weight:	485 kg
Related product line:	V-Press
Type of consumables:	Strapping tape
Press material:	Plastic film, Mixed paper, Cardboard

BALE INFORMATION

Length x Width x Height:	800 x 600 x 600 mm
Weight:	70 kg

