THE CROCODILE.

SEPARATION I PACK

Dewatering system for separating non-acidic liquids (water, beer) from PET bottles, aluminum cans, tin cans and tetra packs.

Model variant for separating large quantities of liquids.

Used for daily processing of small to very large quantities.

Suitable for small to very large packaging sizes.

CROCODILE 200 SEPARATION I PACK

Throughput for 0.5 liter PET bottles [1]	**up to 4.000 pce/h**
Throughput for 1.5 liter PET bottles [1]	**up to 1.100 pce/h**
Throughput for 0.33 liter aluminum cans [1]	**up to 2.500 pce/h**
Throughput for Tetra packs [1]	**up to 2.500 Liter/h**
Container sizes that can be processed [1]	up to 5 Liter
Effective feed opening (L x W)	500 x 600 mm
Channel cross-section	210 x 210 mm
Installation dimensions (L x W x H) [2]	approx. 3.000 x 1.000 x 1.800 mm
Machine weight [2]	approx. 600 kg
Electrical connected load [2]	4,25 kW (16 Amp)
Supply voltage (EU)	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz
Marking	CE

Materials

PET bottles

Aluminum cans, tin cans

TETRA packs, aluminum tubes

HDPE packaging

Industries

Food industry, beverage industry

Breweries, airport catering

Waste management companies

Specialist waste management companies

Options

Closed hood for splash protection

Collecting container for liquids

Storage tank with a capacity of 1,000 liters

Symbol image

[1] Depending on packaging material and viscosity of the liquid [2] Basic machine without options

Subject to technical changes / All specifications without guarantee

sales@heger-world.de / **www.heger-world.de**

CROCODILE 250 SEPARATION I PACK

Throughput for 0.5 liter PET bottles [1]	**up to 9.000 pce/h**
Throughput for 1.5 liter PET bottles [1]	**up to 2.500 pce/h**
Throughput for 0.33 liter aluminum cans [1]	**up to 5.000 pce/h**
Throughput for Tetra packs [1]	**up to 5.000 Liter/h**
Container sizes that can be processed [1]	up to 5 Liter
Effective feed opening (L x W)	500 x 600 mm
Channel cross-section	290 x 290 mm
Installation dimensions (L x W x H) [2]	approx. 3.500 x 1.000 x 1.800 mm
Machine weight [2]	approx. 800 kg
Electrical connected load [2]	7,78 kW (16 Amp)
Supply voltage (EU)	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz
Marking	CE

Materials

PET bottles

Aluminum cans, tin cans

TETRA packs, aluminum tubes

HDPE packaging

Industries

Food industry, beverage industry

Breweries, airport catering

Waste management companies

Specialist waste management companies

Options

Closed hood for splash protection

Collecting container for liquids

Storage tank with a capacity of 1,000 liters

Symbol image

CROCODILE 400 SEPARATION I PACK

Throughput for 0.5 liter PET bottles [1]	**up to 17.000 pce/h**
Throughput for 1.5 liter PET bottles [1]	**up to 4.700 pce/h**
Throughput for 0.33 liter aluminum cans [1]	**up to 10.000 pce/h**
Throughput for Tetra packs [1]	**up to 10.000 Liter/h**
Container sizes that can be processed [1]	up to 10 Liter
Effective feed opening (L x W)	800 x 600 mm
Channel cross-section	400 x 400 mm
Installation dimensions (L x W x H) [2]	approx. 4.950 x 1.270 x 1.810 mm
Machine weight [2]	approx. 2.500 kg
Electrical connected load [2]	15,55 kW (32 / 64 Amp)
Supply voltage (EU)	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz
Marking	CE

Materials

PET bottles

Aluminum cans, tin cans

TETRA packs, aluminum tubes

HDPE packaging

Industries

Food industry, beverage industry

Breweries, airport catering

Waste management companies

Specialist waste management companies

Options

Closed hood for splash protection

Collecting container for liquids

Storage tank with a capacity of 1,000 liters

Symbol image

[1] Depending on packaging material and viscosity of the liquid [2] Basic machine without options

Subject to technical changes / All specifications without guarantee

sales@heger-world.de / **www.heger-world.de**

CROCODILE 500 SEPARATION I PACK

Throughput for 0.5 liter PET bottles [1]	**up to 25.000 pce/h**
Throughput for 1.5 liter PET bottles [1]	**up to 7.000 pce/h**
Throughput for 0.33 liter aluminum cans [1]	**up to 15.000 pce/h**
Throughput for Tetra packs [1]	**up to 15.000 Liter/h**
Container sizes that can be processed [1]	up to 10 Liter
Effective feed opening (L x W)	800 x 600 mm
Channel cross-section	500 x 500 mm
Installation dimensions (L x W x H) [2]	approx. 5.400 x 1.270 x 1.810 mm
Machine weight [2]	approx. 3.200 kg
Electrical connected load [2]	31,10 kW (64 / 80 Amp)
Supply voltage (EU)	3 x 400 V / 50 Hz
Supply voltage (USA)	3 x 480 V / 60 Hz
Marking	CE

Materials

PET bottles

Aluminum cans, tin cans

TETRA packs, aluminum tubes

HDPE packaging

Industries

Food industry, beverage industry

Breweries, airport catering

Waste management companies

Specialist waste management companies

Options

Closed hood for splash protection

Collecting container for liquids

Storage tank with a capacity of 1,000 liters

Symbol image

[1] Depending on packaging material and viscosity of the liquid [2] Basic machine without options

Subject to technical changes / All specifications without guarantee

sales@heger-world.de / **www.heger-world.de**